



PBX IP-PBX

KX-TDE600

Maximum Number of Trunks and Extensions	Total Number of Trunks	Trunk (Physical Trunk Card)	KX-TDE600 (Basic System): 160 KX-TDE600 (2-shelf System): 320 KX-TDE600 (3-shelf System): 480 KX-TDE600 (4-shelf System): 640
		Trunk (Virtual Trunk Card)	KX-TDE600 (Basic System): 64 KX-TDE600 (2-shelf System): 64 KX-TDE600 (3-shelf System): 64 KX-TDE600 (4-shelf System): 64
		Trunk (Virtual Trunk Card) - H.323 trunks	KX-TDE600 (Basic System): 32 KX-TDE600 (2-shelf System): 32 KX-TDE600 (3-shelf System): 32 KX-TDE600 (4-shelf System): 32
		Trunk (Virtual Trunk Card) - SIP trunks	KX-TDE600 (Basic System): 64 KX-TDE600 (2-shelf System): 64 KX-TDE600 (3-shelf System): 64 KX-TDE600 (4-shelf System): 64
	Total Number of Extensions	Extension (Physical Extension Card)	KX-TDE600 (Basic System): 304 KX-TDE600 (2-shelf System): 608 KX-TDE600 (3-shelf System): 880 KX-TDE600 (4-shelf System): 1120
		Extension (Virtual Extension Card)	KX-TDE600 (Basic System): 128 KX-TDE600 (2-shelf System): 128 KX-TDE600 (3-shelf System): 128 KX-TDE600 (4-shelf System): 128
		Extension (Virtual Extension Card) - IP-PT and IP Softphone	KX-TDE600 (Basic System): 128 KX-TDE600 (2-shelf System): 128 KX-TDE600 (3-shelf System): 128 KX-TDE600 (4-shelf System): 128
		Extension (Virtual Extension Card) - SIP Extension	KX-TDE600 (Basic System): 128 KX-TDE600 (2-shelf System): 128 KX-TDE600 (3-shelf System): 128 KX-TDE600 (4-shelf System): 128
Maximum Terminal Equipment	Telephone (using Digital XDP)	SLT	KX-TDE600 (Basic System): 240 KX-TDE600 (2-shelf System): 480 KX-TDE600 (3-shelf System): 720 KX-TDE600 (4-shelf System): 960
		KX-DT300 / KX-T7600 series DPT	KX-TDE600 (Basic System): 256 KX-TDE600 (2-shelf System): 512 KX-TDE600 (3-shelf System): 640 KX-TDE600 (4-shelf System): 640
		Other DPT	KX-TDE600 (Basic System): 128

		KX-TDE600 (2-shelf System): 256 KX-TDE600 (3-shelf System): 384 KX-TDE600 (4-shelf System): 512
	APT	KX-TDE600 (Basic System): 80 KX-TDE600 (2-shelf System): 160 KX-TDE600 (3-shelf System): 240 KX-TDE600 (4-shelf System): 320
	IP-PT	KX-TDE600 (Basic System): 288 KX-TDE600 (2-shelf System): 448 KX-TDE600 (3-shelf System): 608 KX-TDE600 (4-shelf System): 704
	IP-PT - IP-PT*2 (supported by IP-EXT16 card)	KX-TDE600 (Basic System): 160 KX-TDE600 (2-shelf System): 320 KX-TDE600 (3-shelf System): 480 KX-TDE600 (4-shelf System): 640
	IP-PT - IP-PT*3 (supported by IPCEMPR card)	KX-TDE600 (Basic System): 128*4 KX-TDE600 (2-shelf System): 128*4 KX-TDE600 (3-shelf System): 128*4 KX-TDE600 (4-shelf System): 128*4
	SIP Extension	KX-TDE600 (Basic System): 128 KX-TDE600 (2-shelf System): 128 KX-TDE600 (3-shelf System): 128 KX-TDE600 (4-shelf System): 128
DSS console		KX-TDE600 (Basic System): 64 KX-TDE600 (2-shelf System): 64 KX-TDE600 (3-shelf System): 64 KX-TDE600 (4-shelf System): 64
CS	PT interface CS (2-channel) / CS for CSIF card	KX-TDE600 (Basic System): 32 KX-TDE600 (2-shelf System): 64 KX-TDE600 (3-shelf System): 96 KX-TDE600 (4-shelf System): 128
	PT interface CS (8-channel)	KX-TDE600 (Basic System): 16 KX-TDE600 (2-shelf System): 32 KX-TDE600 (3-shelf System): 48 KX-TDE600 (4-shelf System): 64
	IP-CS (8-channel)	KX-TDE600 (Basic System): 16 KX-TDE600 (2-shelf System): 16 KX-TDE600 (3-shelf System): 16 KX-TDE600 (4-shelf System): 16
PS		KX-TDE600 (Basic System): 512 KX-TDE600 (2-shelf System): 512 KX-TDE600 (3-shelf System): 512 KX-TDE600 (4-shelf System): 512
Voice Processing System (VPS)*6		KX-TDE600 (Basic System): 8 KX-TDE600 (2-shelf System): 8 KX-TDE600 (3-shelf System): 8 KX-TDE600 (4-shelf System): 8

	Doorphone	KX-TDE600 (Basic System): 16 KX-TDE600 (2-shelf System): 32 KX-TDE600 (3-shelf System): 48 KX-TDE600 (4-shelf System): 64
	Door Opener	KX-TDE600 (Basic System): 16 KX-TDE600 (2-shelf System): 32 KX-TDE600 (3-shelf System): 48 KX-TDE600 (4-shelf System): 64
	External Sensor	KX-TDE600 (Basic System): 16 KX-TDE600 (2-shelf System): 32 KX-TDE600 (3-shelf System): 48 KX-TDE600 (4-shelf System): 64
	External Relay	KX-TDE600 (Basic System): 16 KX-TDE600 (2-shelf System): 32 KX-TDE600 (3-shelf System): 48 KX-TDE600 (4-shelf System): 64
NOTE	<p>* The maximum number of PTs in the whole system is limited to 640.</p> <p>*1 Even when Digital XDP is used, each shelf supports a maximum of 256 KX-DT300 / KX-t7600 series DPTs.</p> <p>*2 KX-NT300 series (except KX-NT366/KX-NT305), KX-NT265, and KX-NT136.</p> <p>*3 KX-NT400, KX-NT300 series, and KX-NT265 (software version 2.00 or later only).</p> <p>*4 For the KX-NT400, the maximum number of extensions that can be connected to the PBX is 64.</p> <p>*5 One 8-channel PT-interface CS or IP-CS counts as 2 CSs for the total number of CSs.</p> <p>*6 Only a single VPS can be connected to one optional service card.</p>	